

ONESEAL PTW 5.0 CABLE SEALS



Oneseal PTW5 A pull to tighten cable seal with Ø5 mm (3/16") cable and window protection cover

The ideal high security cable seal to apply on all awkward sealing points. Key applications are tank-truck valves, truck trailers, rail wagons, gates etc.

The cable

Flexible galvanised steel cable with high tensile strength. The Ø5 mm cable is non-preformed and unravels if cut. Ink-jet marking for proof of tampering and easy identification. The cable is available in various lengths.

The body

The metal body features a non-flammable shock proof plastic cover and a transparent plastic shield, protecting the engraving against tampering. Standard colours are red and white. Special colours are available for large orders.

Laser engraving.

Your company logo will be engraved by use of high technology laser engraving which prevents tampering. All seals are engraved with a consecutive unique numbering. Bar coding can also be applied.

Packaging

For easy stock control and number verification the seals come in two pieces - cylinders & cables. The cylinders are packed on tape in numerical order together with the cables. For easy handling and distribution 100 seals are packed in 1 inner box. 2 inner boxes are packed in 1 outer box.

Customs

Seals are approved by Customs authorities world wide including US Customs, HM Customs. Seals can only be removed by use of a cable cutter.



Type	Cable width	Cable length	Weight / pcs	Weight / box
PTW5	5 mm	400 mm	0,068 kg	14,3 kg

Packing: 200 pieces per carton.

ISO / PAS 17712

The seal is compliance with ISO / PAS 17712 as High Security and is C-TPAT compliant.

Security seals – a small important detail in shipping - provided by Oneseal an ISO 9001 certified company.